

INSTALLATION INSTRUCTIONS

1. INSTALL THE U-BRAKED LOOK THROUGH THE LAST TWO (2) HOLES OF THE OUTER SITE OF THE SHOE.
2. SLIDE THE LATCH HOLDER WITH THE OPENING FACING TO THE INNER OF THE SHOE OVER THE U-BRACKET LOCK PRESSING SLIGHTLY UNTIL THE END.

(YOU CAN UNINSTALL THE LATCH HOLDER BY REMOVING CLIP N° 1 AND SLIDING THE LATCH HOLDER FROM THE INTERIOR OF THE SHOE TO THE EXTERIOR)

3. INSERT THE CLIP NUMBER 1 WITH THE LEGS FORWARD INTO THE SLOT OF THE LATCH HOLDER PRESSING UNTIL THE LEGS COMPLETELY PAST THROUGH THE BRACKET AND REMAINS ANCHORED.
4. LACE IN THE NEW RUBBER LACES THROUGH THE LACE HOLES OF THE SHOE UNTIL THE END OF THE CORDS GOES THROUGH THE TWO LAST HOLES OF THE INNER SIDE OF THE SHOW. (THERE ARE DIFFERENT LACING TECHNIQUES).
5. FOLD EASY LATCH TO ABOUT 35 DEGREES AND WITH THE NAME FACING THE LATCH HOLDER PASS THE 2 RUBBER LACES TRUTH THE OPENING CHANNELS OF THE EASY LATCH AND CLOSE IT.
6. FLIP EASY LATCH AND WITH THE SLOT FACING UP ANCHOR THE EASY LATCH PET INTO THE LATCH HOLDER, STRETCH THE ELASTIC LACES WITH THE PET ANCHORED IN ITS SUPPORT UNTIL YOUR CHILD IS COMFORTABLE WITH IT BUT THE LACES ARE UNDER TENSION.
7. ONCE THE RUBBER LACES ARE ADJUSTED INSERT THE CLIP NUMBER 2 WITH THE LEGS FORWARD INTO THE SLOT OF THE EASY LATCH AND PRESS HARD UNTIL THE LEGS ARE ANCHORED.
8. ONCE ADJUSTED THE LENGTH OF THE CORDS, CUT THE ENDS AND READY TO USE.

EASY LATCH COMPONENTES

The closing system Easy latch is composed of 5 pieces, three of them are fixed on the shoe or sneaker that act as a support for the Latch which are:

- 1) U BRACKET
- 2) LATCH HOLDER
- 3) CLIP N°1

The Latch is composed of two pieces, one that is the Latch that acts as a guide for the elastic rubber laces and anchoring on the latch holder, the clip N°2 fixes the rubber laces once its length is adjusted:

- 1) Latch
- 2) Clip N°2



